


FEATURES

- Aluminium-alloy IP65 single point load cell.
- Colourless anodized
- Suitable for single and double load cell structured platform scales.
- Maximum platform size: for 50kg-200kg: 600 x 600 mm for 250kg-635kg: 600 x 800 mm

AVAILABLE MODELS


Capacity	Accuracy	Full article description
50 kg	C3	L6W-C3-50kg-3G6
70 kg	C3	L6W-C3-70kg-3G6
100 kg	C3	L6W-C3-100kg-3G6
150 kg	C3	L6W-C3-150kg-3G6
200 kg	C3	L6W-C3-200kg-3G6
250 kg	C3	L6W-C3-250kg-3G6
300kg	C3	L6W-C3-300kg-3G6
500kg	C3	L6W-C3-500kg-3G6
635kg	C3	L6W-C3-635kg-3G6




SPECIFICATION

Accuracy class		OIML R60 C3	
Output sensitivity (=FS)	mV/V	2.0 ± 0.2	
Maximum capacity (E _{max})	kg	50/70/100/150/ 200/ 250/300	500/635
Maximum number of load cell intervals (nLC)		3000	
Ratio of minimum LC verification interval Y=E _{max} / V _{min}		7000	10000
Combined error	%FS	± 0.02	
Safe overload	%FS	120	
Ultimate overload	%FS	150	
Zero balance	%FS	± 2.0	
Excitation, recommended voltage	V	5 ~ 12 (DC)	
Excitation maximum	V	18 (DC)	
Input resistance	Ω	406 ± 6	
Output resistance	Ω	350 ± 3	
Insulation resistance	MΩ	≥ 5000 (50VDC)	
Compensated temperature	°C	-10 ~ +40	
Operating temperature	°C	-35 ~ +65	
Storage temperature	°C	-40 ~ +70	
Element material		Aluminium	
Recommended torque on fixation	N.m	M8: 25	
Ingress protection (acc. to EN 60529)		IP65	

DIMENSIONS IN MM



WIRING



- Shielded, 6 conductor cable
- Cable diameter: Ø4.7mm
- Standard cable length: 3m
- Shield connected to element
- Cable jacket in PU